

Part Number: 39012161 Product Description: Mini-Fit Jr. Plug Housing, Dual Row, 16 Circuits, UL 94V-2, with Panel

Mounting Ears, Natural

Series Number: 5559 Status: Active

Product Category: Connector Housings Engineering Number: 5559-16P

#### **Documents & Resources**

#### **Drawings**

Drawing 039012161\_sd.pdf

**3D Models and Design Files**3D Model 039012161\_stp.zip

#### **Specifications**

Application Specification AS-5557-001-001.pdf
Application Specification 55560001-AS-000.pdf
Packaging Specification PK-5559-001-001.pdf
Product Specification PS-45750-001-001.pdf
Product Specification PS-5556-001-001.pdf
Test Summary 55560010-TS-000.pdf

### **Product Environment Compliance**

#### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# EU RoHS Certificate of Compliance

# **Part Details**

### General

Status	Active
Category	Connector Housings
Series	5559
Description	Mini-Fit Jr. Plug Housing, Dual Row, 16 Circuits, UL 94V-2, with Panel Mounting Ears, Natural
Application	Power, Wire-to-Board, Wire-to-Wire
Comments	Current = 13A max. per circuit when header is mated to a receptacle loaded with 45750 series terminals crimped to 16 AWG wire. See Molex product specification PS-45750-001 for additional current derating information.
Product Family	Mini-Fit Family Power Connectors
Product Name	Mini-Fit Jr.
UPC	800753583979

## Agency

CSA	LR19980
UL	E29179

# Physical

Breakaway	No
Circuits (maximum)	16
Color - Resin	Natural
Flammability	94V-2
Gender	Plug
Glow-Wire Capable	No
Material - Resin	Nylon

Net Weight	4.782/g
Number of Rows	2
Packaging Type	Bag
Panel Mount	Yes
Pitch - Mating Interface	4.20mm
Pitch - Termination Interface	4.20mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40° to +105°C

### Mates With / Use With

# Mates with Part(s)

Description	Part Number
Mini-Fit Jr. Receptacle Housings	<u>5557</u>

## Use with Part(s)

Description	Part Number
Pre-Crimped Lead Mini-Fit Male-to- Mini-Fit Male, Tin (Sn) Plating, 150.00mm Length, 18 AWG, Red	/content/molex/molex-dot- com/us/en/products/product- page.html/797580005.html
Pre-Crimped Lead Mini-Fit Male-to- Mini-Fit Male, Tin (Sn) Plating, 300.00mm Length, 18 AWG, Red	/content/molex/molex-dot- com/us/en/products/product- page.html//97580013.html
Mini-Fit Male Crimp Terminals	<u>5558</u>
Mini-Fit Plus Male Crimp Terminals	<u>46012</u>
Mini-Fit Jr. Crimp Grounding Terminals	<u>30490</u>